

Belcor[®] 575

www.wateradditives.com



All-organic Corrosion Inhibitors for Mild Steel

Description

Belcor 575 is the industry's most powerful mild steel corrosion inhibitor for all-organic cooling water formulations.

Application

Belcor 575 is an aqueous solution of hydroxyl phosphono-acetic acid (HPA), and can be used either on its own or as part of an all organic or low level zinc program.

Benefits

Belcor 575 is a unique high performance mild steel corrosion inhibitor that:

- Is the best available corrosion inhibitor for use in all-organic formulations, as it gives significantly better performance than commodity phosphonates such as HEDP.
- Provides higher biodegradability (93%) and much better environmental profile versus other available programs.
- Provides a positive payback through reduced iron fouling, improved plant integrity and maintenance.
- Increases formulation profitability by replacing costly molybdate.
- Can be easily tested in the field.

Usage

*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

Packaging / Weight

Drum	550 lb	250 kg
IBCs/Totes	3,070 lb	1,300 kg

Bulk quantities available. Consult your sales representative for availability.

Physical Properties

Appearance	Dark brown liquid
Odor	Slight
Active ingredient content	Approx 50% w/w
Specific gravity	1.394-1.445 at 20/20°C
pH of undiluted product	<2
pH (1%) solution	Approx. 1.5
Boiling range (760 mm Hg)	101-103°C (212-217°F)
Freezing point	-5°C (22°F)
Solubility in:	
- Ethylene glycol	Miscible

Further details are available in the safety data sheet



Americas

1979 Lakeside Parkway,
Suite 925
Tucker, GA 30084, USA
Phone +1 678 802 3050
Or 800 600 4523
Fax +1 678 802 3024
Americas@wateradditives.com

Asia Pacific

No. 1 Magazine Road
#04-01, Central Mall Office Tower
Singapore 059567
Phone +65 9745 3227
Fax +65 6234 3606
AsiaPacific@wateradditives.com

Europe

2 Brightgate Way
Stretford, Manchester M32 0TB
United Kingdom
Phone +44 161 864 6699
Fax +44 161 864 6666
Europe@wateradditives.com

MENA

DMCC Dubai Branch
Office 1802, Level 18
Jumeirah Bay X3 Tower, Cluster X
Jumeirah Lake Towers
P.O. Box 263164, Dubai, UAE
Phone +971 4 880 7336
Fax +971 4 880 7404
MiddleEast@wateradditives.com

Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo. © Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.