

# Flocon<sup>®</sup> 190

www.wateradditives.com



## Antiscalant for Reverse Osmosis Systems

### Description

Flocon 190 is a solution of an organic phosphonate. Flocon 190 is highly effective in controlling the deposition of inorganic scale forming salts on membrane surfaces.

- Excellent control of carbonate and sulphate scales for cost effective operation
- Will not adversely interact with polymeric coagulant aids
- Compatible with all major membranes
- International potable water approvals

### Application

Flocon 190 is a solution of an organic phosphonate. Appropriate dosing equipment should be used. Examples of suitable materials are 316L stainless steel, or plastics such as GRP, PVC and PE.

The recommended injection point is into the feedwater downstream of any filtration equipment and cartridge filters.

### Usage

Flocon 190 is miscible with water in all proportions. It may be applied as the neat product, or as a solution in permeate. A minimum dosing solution strength of 10% w/w is recommended.

Flocon 190 should be dosed continuously and proportionately to the feed water flow, to maintain the recommended dose level.

The dose level required is dependent on the quality of the feedwater and the saturation indices of the various scale forming species present in the concentrated brine. Proprietary computer software is used to calculate scaling indices and calculate optimum system recovery. Dose level projections and recommendations are available on request.

\*Please consult with your BWA Water Additives representative to determine optimal dosage recommendations for your system.

### Packaging / Weight

Pail	55 lb	25 kg
Drum	528 lb	240 kg
IBCs/Totes		1200 kg

\*Consult your sales representative for availability.

### Physical Properties

Appearance	Colourless to pale yellow liquid
pH	> 10
Specific gravity at 20/20°C	1.22 to 1.32
Freezing point range	0 to -3 °C

Further details are available in the safety data sheet



## Americas

1979 Lakeside Parkway,  
Suite 925  
Tucker, GA 30084, USA  
Phone +1 678 802 3050  
Or 800 600 4523  
Fax +1 678 802 3024  
Americas@wateradditives.com

## Asia Pacific

No. 1 Magazine Road  
#04-01, Central Mall Office Tower  
Singapore 059567  
Phone +65 9745 3227  
Fax +65 6234 3606  
AsiaPacific@wateradditives.com

## Europe

2 Brightgate Way  
Stretford, Manchester M32 0TB  
United Kingdom  
Phone +44 161 864 6699  
Fax +44 161 864 6666  
Europe@wateradditives.com

## MENA

DMCC Dubai Branch  
Office 1802, Level 18  
Jumeirah Bay X3 Tower, Cluster X  
Jumeirah Lake Towers  
P.O. Box 263164, Dubai, UAE  
Phone +971 4 880 7336  
Fax +971 4 880 7404  
MiddleEast@wateradditives.com

### Patents:

BWA Water Additives (BWA) owns or is the licensee of patents and patent applications, which may cover the products and/or uses described in this brochure.

The following are registered trademarks of BWA Belclene, Belcor, Belgard, Belite, Bellacide, Bellasol, Belsperse, BromiCide, Flocon, Geogard and Liquibrom Drop and Swirl logo. © Registered US Patent and Trademark Office. © 2016 BWA all rights reserved.

The information contained in this product sheet is based on data available to BWA Water Additives at the time of publication. While BWA has made every effort to ensure this information is correct, no responsibility can be accepted by BWA for any loss or liability occasioned by any person acting or refraining from acting as a result of the contents of this publication. BWA cannot guarantee that the results described in this information will be achieved by others if BWA has not participated in the testing process. BWA therefore makes no warranty of merchantability or fitness for a particular purpose or any express or implied warranty in respect of this information. This information is intended for use by technically trained personnel at their discretion and risk and is not a substitute for specific professional or technical advice. BWA's liability shall be limited by its standard limitations of liability contained within its standard terms and conditions of sale if BWA makes any sales to you.

© 2016 all rights reserved. No part of this publication may be reproduced or transmitted in any form or by any means or stored in any retrieval system without the prior written permission of BWA Water Additives UK Limited. BWA Water Additives UK Limited is a private limited company registered in England and Wales at 2 Brightgate Way, Manchester M32 0TB, Registered No. 5657343.